SAFETY DATA SHEET

PLUS GAS

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name PLUS GAS
Product number A1220

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubricant.

1.3. Details of the supplier of the safety data sheet

Supplier Saint Gobain Abrasives

Doxey Road Stafford England ST16 1EA 01785 222000

www.saint-gobain.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0) 777 8505 330

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards

Aerosol 1 - H222, H229 Aerosol 1 - H222, H229

Health hazards

Skin Irrit. 2 - H315 STOT SE 3 - H336 STOT SE 3 - H336

Environmental hazards

Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC)

Xi;R38. F+;R12. N;R51/53. R67.

2.2. Label elements

Pictogram







Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated H229 Pressurised container: may burst if heated

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H222 Extremely flammable aerosol.

Precautionary statements

Revision date: 04/02/2015 Revision: 2.0 Supersedes date: 12/06/2013

PLUS GAS

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing vapour/spray.

P264 Wash contaminated skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local regulations.

Contains KEROSINE (PETROLEUM), HYDRODESULFURIZED

Supplementary precautionary statements

P273 Avoid release to the environment.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

KEROSINE (PETROLEUM), HYDRODESULFURIZED

60-100%

Classification

Classification (67/548/EEC or 1999/45/EC)

Skin Irrit. 2 - H315 Xn;R65. Xi;R38. N;R51/53. R67.

STOT SE 3 - H336 Asp. Tox. 1 - H304 STOT SE 3 - H336

Aquatic Chronic 2 - H411

WHITE MINERAL OIL (PETROLEUM)

5-10%

Classification

Classification (67/548/EEC or 1999/45/EC)

Asp. Tox. 1 - H304 Xn;R65.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

Ingestion

Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention if any discomfort continues.

Skin contact

Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eve contact

Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Vapours may cause drowsiness and dizziness.

Ingestion

May cause discomfort if swallowed.

Skin contact

Irritating to skin.

Eye contact

May cause discomfort.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards

Extremely flammable aerosol. Pressurised container: may burst if heated

Hazardous combustion products

Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO2).

5.3. Advice for firefighters

Protective actions during firefighting

Use water to keep fire exposed containers cool and disperse vapours.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Wear protective clothing and gloves. Provide adequate ventilation. Avoid inhalation of vapours and contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions

Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Eliminate all sources of ignition. Provide adequate ventilation. Absorb spillage with inert, damp, non-combustible material.

6.4. Reference to other sections

Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves. Avoid contact with skin and eyes. Do not breathe vapour/spray. Do not expose to temperatures exceeding 50°C/122°F. Provide adequate ventilation. Keep container in a well-ventilated place. Do not pierce or burn, even after use. Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store at temperatures between 4°C and 40°C.

Storage class

Flammable compressed gas storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

KEROSINE (PETROLEUM), HYDRODESULFURIZED

Long-term exposure limit (8-hour TWA): OES 300 mg/m3

KEROSINE (PETROLEUM), HYDRODESULFURIZED (CAS: 64742-81-0)

DNEL - Oral; Long term : 19 mg/kg/day

8.2. Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Rubber (natural, latex). Neoprene. Polyvinyl chloride (PVC).

Hygiene measures

Wash hands thoroughly after handling.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

Aerosol.

Colour

Clear.

Odour

Mild. Solvent.

Solubility(ies)

Insoluble in water.

9.2. Other information

Other information

Not determined.

SECTION 10: Stability and reactivity

10.1. Reactivity

There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability

Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Not determined.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid

Flammable/combustible materials.

10.6. Hazardous decomposition products

Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation

Vapours may cause drowsiness and dizziness.

Ingestion

Gastrointestinal symptoms, including upset stomach.

Skin contact

Irritating to skin. Prolonged contact may cause redness, irritation and dry skin.

Eye contact

May cause temporary eye irritation.

SECTION 12: Ecological Information

Ecotoxicity

Toxic to aquatic life with long lasting effects.

12.1. Toxicity

Acute toxicity - fish

Not determined.

Ecological information on ingredients.

KEROSINE (PETROLEUM), HYDRODESULFURIZED

Acute toxicity - fish

LC₅₀, 96 hours: 2 - 5 mg/l, Fish

Acute toxicity - aquatic invertebrates

EC₅₀, 48 hours: 1.4 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 1 - 3 mg/l, Algae

Chronic toxicity - fish early life stage

, 28 days: .098 mg/l, Onchorhynchus mykiss (Rainbow trout)

Chronic toxicity - aquatic invertebrates

, 21 days: 0.89, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability

The product is expected to be biodegradable.

12.3. Bioaccumulative potential

The product is not bioaccumulating.

12.4. Mobility in soil

Mobility

The product has poor water-solubility.

12.5. Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

KEROSINE (PETROLEUM), HYDRODESULFURIZED

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950 UN No. (IMDG) 1950 UN No. (ICAO) 1950 UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name

AEROSOLS

(ADR/RID)

Proper shipping name

AEROSOLS

(IMDG)

Proper shipping name AEROSOLS

(ICAO)

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1
IMDG class 2.1
ICAO class/division 2.1
ADN class 2.1

Transport labels



14.4. Packing group

ADR/RID packing group 5F

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



Yes.

14.6. Special precautions for user

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended).

EU legislation

Commission Regulation (EU) No 453/2010 of 20 May 2010. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance

Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date 04/02/2015

Revision 2.0

Supersedes date 12/06/2013

Risk phrases in full

R12 Extremely flammable.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.