

Email: sales@solderconnection.co.uk | Tel: +44(0)1291 624 400

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Version 5.0: Revision date: 15/09/20

SECTION 1: Identification of the substance / mixture and of the company / undertaking

1.1 Product identifiers

Product name: Fluxite Soldering Flux Paste

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use: Soldering metal joints. Industrial uses [SU3];

Professional uses [SU22].

Uses advised against: Any other than the identified use.

1.3 Details of the supplier of the safety data sheet

Company: The Solder Connection

Unit 5 Severn Link Distribution Centre

Chepstow

Monmouthshire NP16 6UN

Telephone: +44 (0) 1291 624400

E-mail address: sales@solderconnection.co.uk
Website: www.solderconnection.co.uk

1.4 Emergency phone number:

+44 (0) 1291624400 09:00 – 17:00 Hrs. Monday - Friday

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture


Classification according to regulation (EC) No 1272/2008

Acute Tox. 4: H302; Skin Corr. 1B: H314; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; STOT SE 3: H335: C > 5 %

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms



Email: sales@solderconnection.co.uk | Tel: +44(0)1291 624 400



Signal word Danger

Hazard statement(s):

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H335	May cause respiratory irritation
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

•

Precautionary statements:

P260	Do not breathe dust/fume/gas/mist/vapours/spray
P261	Avoid breathing dust/fumes/gas/mist/vapours/spray
P264	Wash hands thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P271	Use only outdoors or in well-ventilated areas
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face
	protection

P301 + P330 + P312 + P331 – IF SWALLOWED: Rinse mouth. Call a POISON CENTRE/doctor if you feel unwell. Do NOT induce vomiting.

P303 + P361 + P353 – IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

 $P304 + P310 + P340 - IF\ INHALED:\ Immediately\ call\ a\ POISON\ CENTRE\ or\ doctor/physician.$

Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P363 – Wash contaminated clothing before use.

P391 – Collect spillage. Hazardous to the aquatic environment.

P403 + P233 – Store in a well-ventilated place. Keep container tightly closed.

P405 – Store locked up.

P501 – Dispose of contents/container to all local/regional/national/international regulations.


Supplemental Hazard Information N/A

2.3 Other hazards None known

solderconnect

www.solderconnection.com

in The Solder Connection



Email: sales@solderconnection.co.uk | Tel: +44(0)1291 624 400

SECTION 3: Composition/Information on ingredients

3.2 Mixtures

Component	Classification according to Regulation (EC) No 1278/2008 (CLP)	Conc (%w/w)
Zinc chloride (Zinc chloride, fun	ne) STOT SE 3; H335: C ≥ 5 %	
CAS No 7647-85-7	Skin Corr. 1B: H314;	10-15
EC No 231-592-0	Aquatic Acute 1: H400;	
Index No 030-003-00-2	Aquatic Chronic 1: H410;	
REACH Registration No.	Acute Tox. 4: H302;	
01-2119472431-44-xxxx	STOT SE 3; H335: C ≥ 5 %	

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor/physician in attendance.

Following inhalation

If breathed in, move person into fresh air. Seek medical attention. If breathing is difficult give oxygen.

Following skin contact

Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

Following eye contact

Seek medical attention. Rinse immediately with plenty of water for 15 minutes.

Following ingestion

DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious person. Rinse mouth with water (only if the person is conscious). Seek medical advice immediately and show this container or label.

4.2 Most important symptoms and effects, both acute and delayed

Causes severe inflammation and may damage the cornea. Inhalation may cause shortness of breath. Ingestion may cause nausea and vomiting.

4.3 Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. If swallowed seek medical attention immediately and show this container or label.


SECTION 5: Firefighting measures

5.1 Extinguishing media



www.solderconnection.com

in The Solder Connection



Email: sales@solderconnection.co.uk | Tel: +44(0)1291 624 400

Use as appropriate: Carbon dioxide (CO2), Dry chemical. Foam.

Unsuitable extinguishing media

N/A

5.2 Special hazards arising from the substance or mixture

Corrosive. Burning produce irritating, toxic and obnoxious fumes.

5.3 Advice for firefighters

Wear suitable respiratory equipment when necessary.

5.4 Further information

N/A

SECTION 6: Accidental release measures

6.1 Personal precautions, protection equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment.

Evacuate personnel to a safe area. Advice for emergency responders: For personal protection see Section 8.

6.2 Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3 Methods and material for containment and cleaning up

Stop leak if without risk. Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

6.4 Reference to other sections

For disposal see Section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.

7.2 Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers. Store in original container.


7.3 Specific end use

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Component	CAS No.	Workplace Exposure Limit			Basis	
		Long-term exposure		Short-tern	n exposure	
		limit (8-hr TWA)		limit (8-hr TWA) limit (15 minute)		
		ppm	mg/m ³	ppm	mg/m ³	



Email: sales@solderconnection.co.uk | Tel: +44(0)1291 624 400

Zinc chloride (Zinc	7647-85-7	-	1	-	2	UK. EH40 WEL
chloride, fume)						 Workplace
						Exposure Limit

8.2 Exposure controls

8.2.1 Appropriate engineering controls:

Ensure adequate ventilation of the working area. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits. Ensure the eyewash stations and safety showers are close to the workstation location.

8.2.2 Personal protective equipment

Wear chemical protective clothing.

8.2.2.1 Eye and face protection:

Approved safety goggles required.

8.2.2.2 Skin protection:

Chemical resistant gloves (PVC)

Other skin protection:

Wear appropriate chemical resistant clothing.

Use as appropriate: Personal protective equipment for the body should be selected based on the task being performed and the risk involved and should be approved by a specialist before handling this product.

8.2.2.3 Respiratory protection:

Self-contained breathing apparatus.

8.2.2.4 Thermal hazards:

Wear appropriate thermal protective clothing, when necessary.


8.2.3 Environmental exposure controls:

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Solid
Colour	Amber
Odour	Characteristic
рН	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Evaporation rate	No data available
Flammability rate	No data available
Vapour flammability	No data available



Email: sales@solderconnection.co.uk | Tel: +44(0)1291 624 400

Upper Explosive Limit	No data available
Lower Explosive Limit	No data available
Vapour pressure	No data available
Vapour density	No data available
Relative density	No data available
Fat solubility	No data available
Partition coefficient	No data available
Auto ignition temperature	No data available
Oxidising	No data available
Solubility	Slightly soluble in water

9.2 Other safety information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene content	No data available
Lead content	No data available
VOC (Volatile Organic Compounds)	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

Stable under normal storage and transport conditions.

10.3 Possibility of hazardous reactions

N/A

10.4 Conditions to avoid

N/A

10.5 Incompatible materials

N/A

10.6 Hazardous decomposition products

In the event of fire: See Section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Causes burns.

11.1.3 Hazard information

No data is available on this product.


11.1.4 Toxicological information

Oral Rat LD50: 350 mg/kg Oral Mouse LD50: 329 mg/kg



www.solderconnection.com





Email: sales@solderconnection.co.uk | Tel: +44(0)1291 624 400

11.1.9 Delayed and immediate effects as well as chronic effects from short and long-term exposure

No data is available on this product.

SECTION 12: Ecological information

12.1 Toxicity

Daphnia EC50/48h: 2800 mg/l **Daphnia LC50/96h:** 0.06791 mg/l

Rainbow trout LC50/96h: 0.066 mg/l

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

The generation of waste should be avoided or minimised wherever possible. Avoid dispersal of Spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

SECTION 14: Transport information

Hazard Pictograms




14.1 UN number UN 1760

14.2 UN proper shipping name CORROSIVE LIQUID, N.O.S

14.3 Transport hazard class

ADR/RID 8 Subsidiary risk -



Email: sales@solderconnection.co.uk | Tel: +44(0)1291 624 400

IMDG 8
Subsidiary risk IATA 8

Subsidiary risk -

14.4 Packing group III

14.5 Environmental hazards

Environmental hazards Yes Marine pollutant Yes

ADR/RID

Hazard ID 80 Tunnel Category (E)

IMDG

EmS Code F-A-S-B

IATA

Packing Instruction (cargo) 856
Maximum quantity 60 L
Packing instruction (passenger) 852
Maximum quantity 5 L

14.6 Special precautions for user No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Full text of H-Statements referred to under Sections 2 and 3

H302 Harmful if swallowed


H314 Causes severe skin burns and eye damage

H335 May cause respiratory irritation

H400 Very toxic to aquatic life

H410 Very toxic to aquatic life with long lasting effects

The information in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the



Email: sales@solderconnection.co.uk | Tel: +44(0)1291 624 400

specific material designated and may not be valid for such material used in combination with any other materials or in any other process.