Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

3-IN-ONE® White Lithium Grease

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

WD-40 Company Limited PO Box 440 GB-Kiln Farm, Milton Keynes, MK11 3LF

Tel.: +44 (0) 1908 555400 Fax: +44 (0) 1908 266900 E-Mail: Compliance@wd40.co.uk Homepage: www.wd40.co.uk

WD-40 Company Limited Noorderpoort 93E NL- 5916PJ Venlo

Tel.: +31 85 487 46 91

(RL)

Euro Car Parts Team P. R. Reilly Unit K Furry Park Industrial Est. Swords Road Turnapin Little Dublin 9 D09 TC1

Email: custservice.ie@eurocarparts.com Phone: 1800 818 440

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.: +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week) +353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+44 20 3807 3798 ®

+353 1 901 4670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking. EUH208-Contains (R)-p-mentha-1,8-diene. May produce an allergic reaction.

Without adequate ventilation, formation of explosive mixtures may be possible. Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substances

n.a. 3.2 Mixtures

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2%	
aromatics	
Registration number (REACH)	01-2119463258-33-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	919-857-5
CAS	

content %	30-<50
Classification according to Regulation (EC) 1272/2008 (CLP), M-	EUH066
factors	Flam. Liq. 3, H226
	STOT SÉ 3, H336
	Asp. Tox. 1, H304
Zinc oxide	

01-2119463881-32-XXXX
030-013-00-7
215-222-5
1314-13-2
1-<5
Aquatic Acute 1, H400 (M=1)
Aquatic Chronic 1, H410 (M=1)

(R)-p-mentha-1,8-diene	
Registration number (REACH)	
Index	601-096-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	227-813-5
CAS	5989-27-5
content %	0,1-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 3, H226
factors	Skin Irrit. 2, H315
	Skin Sens. 1B, H317
	Asp. Tox. 1, H304
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 3, H412

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. The following may occur: Irritation of the respiratory tract

Coughing

Page 4 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.09.2022 / 0009 Replacing version dated / version: 01.11.2021 / 0008 Valid from: 26.09.2022 PDF print date: 26.09.2022 3-IN-ONE® White Lithium Grease

Headaches Dizziness Effects/damages the central nervous system Coordination disorders with long-term contact: Product removes fat. Drying of the skin. Dermatitis (skin inflammation) Allergic reaction possible. Ingestion: Nausea Vomiting Danger of aspiration. Oedema of the lungs Other dangerous properties cannot be ruled out. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. 4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media CO2 Extinction powder Water jet spray Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

GB (RL)

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Toxic gases Danger of bursting (explosion) when heated Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous. Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

GB (RL) Page 5 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.09.2022 / 0009 Replacing version dated / version: 01.11.2021 / 0008 Valid from: 26.09.2022 PDF print date: 26.09.2022 3-IN-ONE® White Lithium Grease If spray or gas escapes, ensure ample fresh air is available. Without adequate ventilation, formation of explosive mixtures may be possible. Active substance: Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. 6.4 Reference to other sections For personal protective equipment see Section 8 and for disposal instructions see Section 13. **SECTION 7: Handling and storage** In addition to information given in this section, relevant information can also be found in section 8 and 6.1. 7.1 Precautions for safe handling 7.1.1 General recommendations Ensure good ventilation. Avoid inhalation of the vapours. Avoid contact with eyes or skin. Keep away from sources of ignition - Do not smoke. Take measures against electrostatic charging, if appropriate. Do not use on hot surfaces. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use. Use working methods according to operating instructions. 7.1.2 Notes on general hygiene measures at the workplace General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed. 7.2 Conditions for safe storage, including any incompatibilities Keep out of access to unauthorised individuals. Not to be stored in gangways or stair wells. Store product closed and only in original packing. Do not store with flammable or self-igniting materials. Observe special regulations for aerosols! Observe special storage conditions. Observe special storage conditions. Keep protected from direct sunlight and temperatures over 50°C. Store in a well ventilated place. Store cool. 7.3 Specific end use(s) No information available at present. SECTION 8: Exposure controls/personal protection 8.1 Control parameters Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3 ^(B) Chemical Name Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics WEL-TWA: 800 mg/m3 WEL-STEL: ---Monitoring procedures: Draeger - Hydrocarbons 0,1%/c (81 03 571) Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) BMGV: ---Other information: (OEL acc. to RCPmethod, paragraphs 84-87, EH40) Chemical Name Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics OELV-15min: OELV-8h: 100 ppm (573 mg/m3) ("Stoddard ---solvent", [White spirit]) Draeger - Hydrocarbons 0,1%/c (81 03 571) Monitoring procedures: Draeger - Hydrocarbons 2/a (81 03 581)

Compur - KITA-187 S (551 174)

Other information:

BLV: ---

Chemical Name

Petroleum gases, liquefied

- (R) - Page 6 of 19 Safety data sheet according Revision date / version: 26.0 Replacing version dated / ve Valid from: 26.09.2022 PDF print date: 26.09.2022 3-IN-ONE® White Lithium G	ersion: 01.11.2021 / 0008	2006, Annex II				
WEL-TWA: 1000 ppm (175 petroleum gas (LPG))	iquefied					
Monitoring procedures: BMGV:			Other info	mation:		
	Detectory was a line	- <i>t</i> '1		mation.		
Chemical Name OELV-8h:	Petroleum gases, lique	ELV-15min: 1000 ppm (Butane)			
Monitoring procedures:						
BLV:			Other info	rmation:		
Chemical Name	Oil mist, mineral				1	
WEL-TWA: 5 mg/m3 (Mine metal working fluids, ACGIH		EL-STEL:				
Monitoring procedures:	- Draeç	ger - Oil Mist 1/a (67 33 0				
BMGV:			Other info	rmation:		
Chemical Name OELV-8h: 5 mg/m3 (Miner severely refined (inhalable))		ELV-15min:				
Monitoring procedures:		ger - Oil Mist 1/a (67 33 0				
BLV:			Other infor	rmation:		
Hvdrocarbons, C9-C11, n-a	alkanes, isoalkanes, cyclics	s. <2% aromatics				
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	900	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	125	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	185	mg/m3	
Consumer	Human - oral Human - dermal	Long term, systemic effects	DNEL	125 300	mg/kg bw/day	
Workers / employees		Long term, systemic effects			mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1500	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	208	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	871	mg/m3	
Zinc oxide Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
Area of application	Environmental compartment	Enect on health	r	value	Unit	Note
	Environment - freshwater		PNEC	20,6	µg/l	
	Environment - marine Environment - sewage		PNEC PNEC	6,1 100	μg/l μg/l	
	treatment plant					
	Environment - sediment, freshwater		PNEC	117,8	mg/kg dw	
	Environment - sediment, marine		PNEC	56,5	mg/kg dw	
Canaura	Environment - soil	Chart tarra 1	PNEC	35,6	mg/kg dw	
Consumer	Human - inhalation	Short term, local effects	DNEL	3,1	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,5	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg	

GB (RL)

Consumer	Human - inhalation Long term, systemic effects				mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,83	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg bw/day	
Workers / employees	/ employees Human - dermal S		DNEL	6223	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, local effects	DNEL	83	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,5	mg/m3	
Workers / employees	Human - oral	Short term, local effects	DNEL	62,2	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	6,2	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5	mg/m3	

Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	14	µg/l	
	Environment - marine		PNEC	1,4	µg/l	
	Environment - sewage treatment plant		PNEC	1,8	mg/l	
	Environment - sediment, freshwater		PNEC	3,85	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,3851	mg/kg dry weight	
	Environment - soil		PNEC	0,763	mg/kg dry weight	
	Environment - oral (animal feed)		PNEC	133	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	66,7	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	9,5	mg/kg body weight/day	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |

OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU. (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).

BLV = Biological limit value |

GB (RL)

Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and nonmetrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN ISO 374).

If applicable

Protective Neoprene® / polychloroprene gloves (EN ISO 374).

Minimum layer thickness in mm:

1

Permeation time (penetration time) in minutes:

>= 480

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm: 0.4

Permeation time (penetration time) in minutes:

>= 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. If OES or MEL is exceeded. Filter A2 P2 (EN 14387), code colour brown, white At high concentrations: Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138) Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range: Flammability: Lower explosion limit: Upper explosion limit: Flash point: Auto-ignition temperature: Decomposition temperature: pH: Kinematic viscosity: Solubility: Partition coefficient n-octanol/water (log value): Vapour pressure: Density and/or relative density: Relative vapour density: Particle characteristics: 9.2 Other information

9.2 Other Informatio Explosives:

Aerosol. Active substance: liquid. White Characteristic There is no information available on this parameter. There is no information available on this parameter. Does not apply to aerosols. There is no information available on this parameter. There is no information available on this parameter. Does not apply to aerosols. Does not apply to aerosols. There is no information available on this parameter. Mixture is non-soluble (in water). >20,5 mm2/s (40°C) Not miscible Does not apply to mixtures. There is no information available on this parameter. Does not apply to aerosols. Does not apply to aerosols. Does not apply to aerosols.

When using: development of explosive vapour/air mixture possible. No

Oxidising liquids:

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** See also section 7. Heating, open flame, ignition sources Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Foxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.

Skin corrosion/irritation:	Repeated exposure may cause skin dryness or cracking.
Serious eye	n.d.a.
damage/irritation:	
Respiratory or skin	n.d.a.
sensitisation:	
Germ cell mutagenicity:	n.d.a.
Carcinogenicity:	n.d.a.
Reproductive toxicity:	n.d.a.
Specific target organ toxicity -	n.d.a.
single exposure (STOT-SE):	
Specific target organ toxicity -	n.d.a.
repeated exposure (STOT-	
RE):	
Aspiration hazard:	n.d.a.
Symptoms:	n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	>18,5	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Rat	OECD 478 (Genetic Toxicology - Rodent dominant Lethal Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative, Analogous conclusion Chinese hamster
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Carcinogenicity:	NOAEC	1100	mg/m3	Mouse	OECD 453 (Combined Chronic Toxicity/Carcinogenicit y Studies)	Female

(B) (B) Page 11 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.09.2022 / 0009 Replacing version dated / version: 01.11.2021 / 0008 Valid from: 26.09.2022 PDF print date: 26.09.2022 3-IN-ONE® White Lithium Grease

Carcinogenicity:	NOAEC	>= 2200	mg/m3	Mouse	OECD 453 (Combined Chronic Toxicity/Carcinogenicit y Studies)	Male
Reproductive toxicity (Effects on fertility):	NOAEL	>= 3000	mg/kg bw/d	Rat	OECD 415 (One- Generation Reproduction Toxicity Study)	Male
Reproductive toxicity (Effects on fertility):	NOAEL	>= 1500	mg/kg bw/d	Rat	OECD 415 (One- Generation Reproduction Toxicity Study)	Female
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness., STOT SE 3, H336
Aspiration hazard:						Yes
Symptoms:						unconsciousnes s, headaches, dizziness, discoloration of the skin, vomiting, diarrhoea
Specific target organ toxicity - repeated exposure (STOT- RE), oral:	NOAEL	3000	mg/kg/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT- RE), inhalat.:	NOAEC	1444	ppm	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Analogous conclusion

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>15000	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,7	mg/l/4h	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					(Ames-Test)	Negative
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
					Test)	
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative
					Mammalian	Chinese
					Chromosome	hamster
					Aberration Test)	
Germ cell mutagenicity:				Mouse	OECD 474	Negative
					(Mammalian	
					Erythrocyte	
					Micronucleus Test)	
Reproductive toxicity:				Rat	OECD 416 (Two-	Negative,
					generation	Analogous
					Reproduction Toxicity	conclusion
					Study)	

Symptoms:			breathing
			difficulties,
			chest pain
			(thorax pain),
			diarrhoea,
			fever, joint
			pain, coughing,
			headaches,
			circulatory
			disorders,
			metal fume
			fever, muscle
			pains, mucous
			membrane
			irritation,
			nausea and
			vomiting.

(R)-p-mentha-1,8-diene				·	· - · · ·	
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	> 2000	mg/kg	Rat	OECD 423 (Acute	Female
					Oral Toxicity - Acute	
					Toxic Class Method)	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit		Skin Irrit. 2
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
C C					Irritation/Corrosion)	
Respiratory or skin				Mouse	OECD 429 (Skin	Skin Sens. 1B
sensitisation:					Sensitisation - Local	
					Lymph Node Assay)	
Respiratory or skin				Mouse	OECD 429 (Skin	Skin Sens. 1
sensitisation:					Sensitisation - Local	
					Lymph Node Assay)	
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative
Com com managemeny:					Mammalian Cell Gene	linguare
					Mutation Test)	
Germ cell mutagenicity:					OECD 479 (Genetic	Negative
Com com managemeny:					Toxicology - In Vitro	Chinese
					Sister Chromatid	hamster
					Exchange assay in	namotor
					Mammalian Cells)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
Com con matagomony.					Mammalian	Chinese
					Chromosome	hamster
					Aberration Test)	namotor
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
Germ cen matagementy.				typhimurium	Reverse Mutation	Negative
				typinnunun	Test)	
Symptoms:					1000	diarrhoea,
Cymptomo.						rash, itching,
						gastrointestina
						disturbances,
						mucous
						membrane
						irritation.
						, ,
						nausea and
						vomiting.

Course in teams of		ali a uula a a a
Symptoms:		diarrhoea,
		rash, itching,
		gastrointestinal
		disturbances,
		mucous
		membrane
		irritation,
		nausea and
		vomiting.

Petroleum gases, liquefied									
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by inhalation:	LC50	>5	mg/l						
Skin corrosion/irritation:						Not irritant			
Serious eye						Not irritant			
damage/irritation:									
Respiratory or skin						No (skin			
sensitisation:						contact)			
Aspiration hazard:						No			

11.2. Information on other hazards

3-IN-ONE® White Lithium	n Grease					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting						Does not apply
properties:						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

3-IN-ONE® White Lithin	um Grease	3-IN-ONE® White Lithium Grease									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes				
12.1. Toxicity to fish:	-						n.d.a.				
12.1. Toxicity to							n.d.a.				
daphnia:											
12.1. Toxicity to algae:							n.d.a.				
12.2. Persistence and							Isolate as				
degradability:							much as				
							possible with				
							an oil separator.				
12.3. Bioaccumulative							n.d.a.				
potential:											
12.4. Mobility in soil:							n.d.a.				
12.5. Results of PBT							n.d.a.				
and vPvB assessment											
12.6. Endocrine							Does not apply				
disrupting properties:							to mixtures.				
12.7. Other adverse							No information				
effects:							available on				
							other adverse				
							effects on the				
							environment.				
Other information:							According to				
							the recipe,				
							contains no				
							AOX.				

Other information:		DOC-
		elimination
		degree(complex
		ing organic
		substance)>=
		80%/28d: n.a.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EL50	48h	0,95	mg/l			QSAR
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,13	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	ErC50	72h	>1000	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EbC50	72h	>1000	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	100	mg/l	Raphidocelis subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.1. Toxicity to algae:	NOELR	72h	3	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.3. Bioaccumulative potential:			5-6,7				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substanc

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and	-						Not relevant for
degradability:							inorganic
							substances.
12.3. Bioaccumulative							Not relevant for
potential:							inorganic
							substances.
12.4. Mobility in soil:	Log Koc		2,2				
12.1. Toxicity to fish:	LC50	96h	1,1-2,5	ppm	Oncorhynchus		
					mykiss		
12.1. Toxicity to fish:	LC50	96h	3,31- 8,062	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	LC50	96h	>320	mg/l	Lepomis		
10.1 Taxiaituta	5050	406	1		macrochirus		
12.1. Toxicity to	EC50	48h	1	mg/l	Daphnia magna	OECD 202	
daphnia:						(Daphnia sp. Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to	EC50	48h	0,413-	mg/l	Ceriodaphnia	U.S. EPA	
daphnia:			0,83		spec.	ECOTOX	
aapinna.			0,00			Database	

12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,058	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	0,17	mg/l	Selenastrum capricornutum		
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,017	mg/l	Pseudokirchnerie Ila subcapitata		
12.1. Toxicity to algae:	EC50	72h	0,136	mg/l	Scenedesmus quadricauda	OECD 201 (Alga, Growth Inhibition Test)	
12.4. Mobility in soil:			158,5	L/kg			
12.5. Results of PBT and vPvB assessment							Not relevant for inorganic substances.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Kow		4,38			OECD 117 (Partition Coefficient (n- octanol/water) - HPLC method)	37 °C, pH = 7.2
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.
12.1. Toxicity to fish:	LC50	96h	0,70	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,307- 0,42	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	ErC50	72h	0,214- 0,32	mg/l	Pseudokirchnerie Ila subcapitata	OEĆD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	96h	4	mg/l			
12.2. Persistence and degradability:		28d	80-92	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	71	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.4. Mobility in soil:						,	Adsorption in ground.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substanc

Petroleum gases, liquefied							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	147,54	mg/l		QSAR	
12.3. Bioaccumulative potential:							Not to be expected

Page 16 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.09.2022 / 0009 Replacing version dated / version: 01.11.2021 / 0008 Valid from: 26.09.2022 PDF print date: 26.09.2022 3-IN-ONE® White Lithium Grease							
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
	ę	SECTION	N 13: Di	sposal c	onsiderations	6	
13.1 Waste treatment methods For the substance / mixture / residual amounts EC disposal code no.: The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 07 06 99 wastes not otherwise specified 16 05 04 gases in pressure containers (including halons) containing hazardous substances Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations. Take full aerosol cans to problem waste collection. Take emptied aerosol cans to valuable material collection. For contaminated packing material Pay attention to local and national official regulations. Recommendation: Do not perforate, cut up or weld uncleaned container. Recording 15 01 04 metallic packaging							
		SECTIC)N 14: T	ransport	t information		
General statement 14.1. UN number or ID n Transport by road	lumber: /by rail (ADF			1950			
14.2. UN proper shipping UN 1950 AEROSOLS 14.3. Transport hazard of 14.4. Packing group: Classification code: LQ: 14.5. Environmental haz Tunnel restriction code;	slass(es):			2.1 - 5F 1 L enviro D	nmentally hazardou	IS	
Transport by sea (IMDG-code) 14.2. UN proper shipping name: AEROSOLS (ZINC OXIDE) 14.3. Transport hazard class(es): 2.1 14.4. Packing group: - EmS: F-D, S-U Marine Pollutant: Yes 14.5. Environmental hazards: environmentally hazardous Transport by air (IATA) 14.2. UN proper shipping name:							
Aerosols, flammable 14.3. Transport hazard class(es): 14.4. Packing group: 14.5. Environmental hazards: Not applicable 14.6. Special precautions for user Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations. Precautions must be taken to prevent damage. 14.7. Maritime transport in bulk according to IMO instruments Freighted as packaged goods rather than in bulk, therefore not applicable. Minimum amount regulations have not been taken into account. Danger code and packing code on request. Comply with special provisions.							

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

(GB) (RL)

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for	referred to in Article 3(10) for
		the application of - Lower-tier	the application of - Upper-tier
		requirements	requirements
E2		200	500
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

~ 83 %

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

EUF0007 Revised sections: 2 Employee training in handling dangerous goods is required. These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking.

STOT SE — Specific target organ toxicity - single exposure - narcotic effects Aquatic Chronic — Hazardous to the aquatic environment - chronic Aerosol — Aerosols Page 18 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.09.2022 / 0009 Replacing version dated / version: 01.11.2021 / 0008 Valid from: 26.09.2022 PDF print date: 26.09.2022 3-IN-ONE® White Lithium Grease

Flam. Liq. — Flammable liquid Asp. Tox. — Aspiration hazard Aquatic Acute — Hazardous to the aquatic environment - acute Skin Irrit. — Skin irritation Skin Sens. — Skin sensitization

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany). EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approximately approx. Article number Art., Art. no. ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BSEF The International Bromine Council body weight bw CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community FC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances **ELINCS** European List of Notified Chemical Substances EN European Norms EPA United States Environmental Protection Agency (United States of America) $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) et cetera etc. EU **European Union** EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc octanol-water partition coefficient Kow International Agency for Research on Cancer IARC IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

GB (RL) Page 19 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.09.2022 / 0009 Replacing version dated / version: 01.11.2021 / 0008 Valid from: 26.09.2022 PDF print date: 26.09.2022 3-IN-ONE® White Lithium Grease IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive IUCLIDInternational Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Log Kow, Log Pow Logarithm of octanol-water partition coefficient LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available NIOSHNational Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development org. organic OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic ΡE Polyethylene PNEC Predicted No Effect Concentration parts per million mag PVC Polyvinylchloride REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical REACH-IT List-No. identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative wwt wet weight The statements made here should describe the product with regard to the necessary safety precautions - they are

not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.