

QUICK DRY BLACK SATIN PAINT

**Page:** 1

Compilation date: 17/04/2013 Revision date: 26/02/2018

Revision No: 5

# Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: QUICK DRY BLACK SATIN PAINT

Product code: BLASQD

Synonyms: BLACK SATIN QUICK DRY

1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road Cricklewood London

NW2 7TX

United Kingdom

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

# **1.4. Emergency telephone number**

Emergency tel: .+44(0)2084504666 (Office hours only)

# Section 2: Hazards identification

2.1. Classification of the substance or mixture			
Classification under CLP:	tion under CLP: Skin Sens. 1: H317; -: EUH208		
Most important adverse effects:	Contains texanol, a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no 247-500-7]		
	and 2-methyl-2h-isothiazol-3-o. May produce an allergic reaction. May cause an allergic		
	skin reaction.		
2.2. Label elements			

Label elements:			
Hazard statements:	EUH208: Contains texanol, a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no		
	247-500-7] and 2-methyl-2h-isothiazol-3-o. May produce an allergic reaction.		
	H317: May cause an allergic skin reaction.		
Hazard pictograms:	GHS07: Exclamation mark		
	<b>∧</b>		

# QUICK DRY BLACK SATIN PAINT

Page: 2

Signal words:WarningPrecautionary statements:P102: Keep out of reach of children.P301+312: IF SWALLOWED: Call a doctor if you feel unwell.P280: Wear protective gloves and eye protection.P262: Do not get in eyes, on skin, or on clothing.P302+352: IF ON SKIN: Wash with plenty of water/soap.P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Removecontact lenses, if present and easy to do. Continue rinsing.

#### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

#### Section 3: Composition/information on ingredients

#### 3.2. Mixtures

#### Hazardous ingredients:

TEXANOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	25265-77-4	-	Aquatic Chronic 3: H412; Skin Sens. 1: H317	1.000%

# Section 4: First aid measures

4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: No data available.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

#### Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Dry chemical powder. Alcohol resistant foam. Water spray. Water fog. Carbon dioxide.

# QUICK DRY BLACK SATIN PAINT

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

# Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	6.1. Personal	precautions,	protective eq	uipment and	emergency	procedures
--	---------------	--------------	---------------	-------------	-----------	------------

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Mechanically ventilate the spillage area whilst avoiding the formation of explosive concentrations - see section 9 of SDS. Do not attempt to take action without suitable protective clothing - see section 8 of SDS.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

#### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Wash the ground with an appropriate self-emulsifying solvent.

6.4. Reference to other sections

# Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is exhaust ventilation of the area. Smoking is forbidden.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from direct sunlight. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Glass. Coated steel.

7.3. Specific end use(s)

# Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

# QUICK DRY BLACK SATIN PAINT

Page: 4

Workplace exposure limits:		xposure limits:	Respirable dust			
	State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL	
	UK	25mg.m-3	-	-	-	

#### **DNEL/PNEC** Values

# DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure a retention tank is installed.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: PVC gloves. Nitrile gloves.

Eye protection: Safety glasses with side-shields.

Skin protection: Protective clothing, PVC.

# Section 9: Physical and chemical properties

State:	Liquid	
Colour:	Black	
Odour:	Low.	
Evaporation rate:	No data available.	
Oxidising:	Non-oxidising (by EC criteria)	
Solubility in water:	Miscible	
Viscosity:	Viscous	
Boiling point/range°C:	No data available. Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available. upper:	No data available.
Flash point°C:	>61 Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available. Vapour pressure:	No data available.
Relative density:	1.16 @ 20 C pH:	7.5-8.0
VOC g/l:	No data available.	

#### 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

# QUICK DRY BLACK SATIN PAINT

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

# 10.4. Conditions to avoid

Conditions to avoid: Heat.

### 10.5. Incompatible materials

Materials to avoid: Oxidising agents. Strong acids.

#### **10.6.** Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

# Section 11: Toxicological information

# 11.1. Information on toxicological effects

#### Relevant hazards for product:

Hazard	Route	Basis
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: No data available.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

#### 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Soluble in water. Readily absorbed into soil. Volatile.

# 12.5. Results of PBT and vPvB assessment

#### **PBT identification:** This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

Other adverse effects: No data available.

# QUICK DRY BLACK SATIN PAINT

# Section 13: Disposal considerations 13.1. Waste treatment methods Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company. NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal. Section 14: Transport information 14.1. UN number UN number: NOT CLASSIFIED 14.2. UN proper shipping name 14.3. Transport hazard class(es) 14.4. Packing group 14.5. Environmental hazards Environmentally hazardous: No Marine pollutant: No 14.6. Special precautions for user Special precautions: No special precautions. Section 15: Regulatory information 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **15.2. Chemical Safety Assessment** Chemical safety assessment: Saftey Data Sheet complies with UK regulatory references in accordance with CHIP 3.1. Section 16: Other information Other information Other information: The product complies with the requirements of the Toy Safety Regulations, BS EN 71 Part 3 1995. A certificate of conformity can be supplied upon request. Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction. H317: May cause an allergic skin reaction. H412: Harmful to aquatic life with long lasting effects. Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any

- damage resulting from handling or from contact with the above product. As the specific
  - conditions of use of the product are outside the supplier's control, the user is

responsible for ensuring that the requirements of relevant legislation are complied with.