

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

EVO-STIK FLOORING ADHESIVE Supercedes Date: 11-Mar-2022

Revision date 05-Sep-2022 Revision Number 3.04

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK FLOORING ADHESIVE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesive

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650

Ireland NPIC - National Poison Information Centre

Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)

Healthcare Professionals: +353 (01) 8092566 (24 hour service)

Europe 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin sensitisation Category 1 - (H317)

2.2. Label elements

Contains 2-methyl-2H-isothiazol-3-one [MIT], 1,2-benzisothiazol-3(2H)-one [BIT], reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]



United Kingdom - BE Page 1 / 13

EVO-STIK FLOORING ADHESIVE Supercedes Date: 11-Mar-2022

Revision date 05-Sep-2022 Revision Number 3.04

Signal word

Warning

Hazard statements

H317 - May cause an allergic skin reaction.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P261 - Avoid breathing vapours

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Combustible liquid.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Potassium hydroxide	215-181-3	1310-58-3	0.1- <1	Acute Tox. 4 (H302) Skin Corr. 1A (H314)	Eye Irrit. 2 :: 0.5%<=C<2% Skin Corr. 1A :: C>=5% Skin Corr. 1B :: 2%<=C<5% Skin Irrit. 2 :: 0.5%<=C<2%	01-2119487136- 33-XXXX
1,2-benzisothiazol-3(2H) -one [BIT]	220-120-9	2634-33-5	0.01 - < 0.05	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Aquatic Acute 1 (H400) Acute Tox. 2 (H330) Aquatic Chronic 2 (H411)	Skin Sens. 1 :: C>=0.05%	01-2120761540- 60-XXXX
2-methyl-2H-isothiazol-3 -one [MIT]	220-239-6	2682-20-4	0.0015 - < 0.0025	Skin Corr. 1B (H314) Eye Dam. 1	Skin Sens. 1 :: C>=0.0015%	01-2120764690- 50-xxxx

United Kingdom - BE Page 2 / 13

EVO-STIK FLOORING ADHESIVE
Supercedes Date: 11-Mar-2022

Revision date 05-Sep-2022 Revision Number 3.04

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation IF exposed or concerned: Get medical advice/attention. Remove to fresh air.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper

eyelids. Consult a doctor.

Skin contact Wash with soap and water. May cause an allergic skin reaction. In the case of skin

irritation or allergic reactions see a doctor.

Ingestion Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never

give anything by mouth to an unconscious person.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of

contamination. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

United Kingdom - BE Page 3 / 13

EVO-STIK FLOORING ADHESIVE Supercedes Date: 11-Mar-2022

Revision date 05-Sep-2022 **Revision Number** 3.04

Symptoms Itching. Rashes. Hives.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Product is or contains a sensitiser. May cause

sensitisation by skin contact.

Hazardous combustion products Carbon oxides.

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Use personal protective equipment as required. See **Personal precautions**

section 8 for more information. Take precautionary measures against static discharges. Do not touch or walk through spilled material. Avoid contact with skin, eyes or clothing.

Ensure adequate ventilation. Keep people away from and upwind of spill/leak.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or **Environmental precautions**

spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dyke

far ahead of liquid spill for later disposal.

Take precautionary measures against static discharges. Dam up. Soak up with inert Methods for cleaning up

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

United Kingdom - BE Page 4 / 13

EVO-STIK FLOORING ADHESIVE Supercedes Date: 11-Mar-2022

Revision date 05-Sep-2022 Revision Number 3.04

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact

with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product.

Take off contaminated clothing and wash it before reuse.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children.

Recommended storage

temperature

Keep at temperatures between 5 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Adhesive.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Limestone	-	TWA: 10 mg/m ³
1317-65-3		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Potassium hydroxide	-	STEL: 2 mg/m ³
1310-58-3		•

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
1,2-benzisothiazol-3(2H)-one [BIT]	(2634-33-5)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.81 mg/m ³	
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d	

Derived No Effect Level (DNEL)				
1,2-benzisothiazol-3(2H)-one	1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m³		
Consumer	Dermal	0.345 mg/kg bw/d		

United Kingdom - BE Page 5 / 13

EVO-STIK FLOORING ADHESIVE Revision date 05-Sep-2022 Supercedes Date: 11-Mar-2022

Long term

Predicted No Effect Concentration No information available. (PNEC)

Predicted No Effect Concentration (PNEC)			
1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	4.03 μg/l		
Marine water	0.403 μg/l		
Sewage treatment plant	1.03 mg/l		
Freshwater sediment	49.9 μg/l		
Marine sediment	4.99 μg/l		
Soil	3 mg/kg dry weight		

8.2. Exposure controls

Systemic health effects

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Avoid contact with eyes. Eye

protection must conform to standard EN 166.

Hand protection Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the

breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves

Revision Number 3.04

depends on the material and the thickness as well as the temperature.

Skin and body protection Wear protective gloves and protective clothing. Avoid contact with skin, eyes or clothing.

Respiratory protection During spraying wear suitable respiratory equipment.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid **Appearance** Paste Brown Colour Organic. Odour

Odour threshold No information available

Remarks • Method Property Values

Melting point / freezing point No data available None known Initial boiling point and boiling 100 °C None known

range **Flammability**

Not applicable for liquids . Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

> 80 °C Flash point None known **Autoignition temperature** No data available None known

Decomposition temperature None known

pН 8 - 10 None known. pH (as aqueous solution) No data available None known Kinematic viscosity No data available None known **Dynamic viscosity** 89000 mPas @ 23 °C Water solubility Miscible in water. None known Solubility(ies) No data available None known

United Kingdom - BE Page 6/13

EVO-STIK FLOORING ADHESIVE

Supercedes Date: 11-Mar-2022

Revision date 05-Sep-2022 **Revision Number** 3.04

Partition coefficient No data available Vapour pressure No data available Relative density 1.27

Bulk Density No data available **Liquid Density** No data available Relative vapour density No data available

Particle characteristics

Particle Size Particle Size Distribution

9.2. Other information

Solid content (%) **VOC** content

No information available

No information available

No information available

< 5 g/L

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

None known

None known

None known

None known

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available. Reactivity

10.2. Chemical stability

Stable under normal conditions. Stability

Explosion data

Sensitivity to mechanical impact

None.

None.

Sensitivity to static discharge

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition

Carbon monoxide. Carbon dioxide (CO2). Hydrocarbons.

products

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

United Kingdom - BE Page 7 / 13

EVO-STIK FLOORING ADHESIVE Supercedes Date: 11-Mar-2022

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact May cause sensitisation by skin contact. Specific test data for the substance or mixture is

not available. Repeated or prolonged skin contact may cause allergic reactions with

Revision date 05-Sep-2022

Revision Number 3.04

susceptible persons. (based on components).

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Potassium hydroxide	=284 mg/kg (Rattus)	-	-
1,2-benzisothiazol-3(2H)-one [BIT]	=670 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	ATE = 0.25 mg/L
2-methyl-2H-isothiazol-3-one [MIT]	LD50 =285 mg/Kg (Rattus)	LD50 >242 mg/Kg (Rattus)	=0.11 mg/L (Rattus) 4 h
reaction mass of 5-chloro-2-methyl-2H-isothiazo I-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	= 53 mg/kg(Rat)	LD50 = 87.12 mg/kg (Oryctolagus cuniculus)	= 0.33 mg/L (Rat) 4h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation May cause sensitisation by skin contact.

2-methyl-2H-isothiazol-3-one [MIT] (2682-20-4)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	Sensitizing
Sensitisation			-

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

United Kingdom - BE Page 8 / 13

EVO-STIK FLOORING ADHESIVE Supercedes Date: 11-Mar-2022 Revision date 05-Sep-2022 Revision Number 3.04

--

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Potassium hydroxide 1310-58-3	-	LC50: =80mg/L (96h, Gambusia affinis)	-	-		
1,2-benzisothiazol-3(2 H)-one [BIT] 2634-33-5		LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006		EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	
2-methyl-2H-isothiazol- 3-one [MIT] 2682-20-4	EC50 (72hr) 0.157 mg/l (Pseudokirchner iella subcapitata) (OECD 201)	, ·	-	EC50 (48hr) 1.68 mg/l (Daphnia) (OECD 202)	10	1
reaction mass of 5-chloro-2-methyl-2H-is othiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1) [C(M)IT/MIT] 55965-84-9	(Pseudokirchner	, ,	-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

12.2. Persistence and degradability

Persistence and degradability No information available.

2-methyl-2H-isothiazol-3-one [MIT] (2682-20-4)

Method	Exposure time	Value	Results
OECD Test No. 308: Aerobic and		Half-life	1.28-2.1 days
Anaerobic Transformation in Aquatic			
Sediment Systems			
OECD Test No. 309: Aerobic		biodegradation Half-life	Readily biodegradable 4.1

United Kingdom - BE Page 9 / 13

Revision date 05-Sep-2022

EVO-STIK FLOORING ADHESIVE Supercedes Date: 11-Mar-2022

Supercedes Date: 11-Mar-2022 Revision Number 3.04

Mineralization in Surface Water - days
Simulation Biodegradation Test

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready	28 days	biodegradation	Not readily biodegradable
Biodegradability: CO2 Evolution Tes	t		
(TG 301 B)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

••	
Chemical name	Partition coefficient
Potassium hydroxide	0.83
1,2-benzisothiazol-3(2H)-one [BIT]	0.7
2-methyl-2H-isothiazol-3-one [MIT]	-0.32
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	0.7
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Potassium hydroxide	The substance is not PBT / vPvB PBT assessment does
·	not apply
1,2-benzisothiazol-3(2H)-one [BIT]	The substance is not PBT / vPvB
2-methyl-2H-isothiazol-3-one [MIT]	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	The substance is not PBT / vPvB
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products

Dispose of waste in accordance with environmental legislation. Dispose of in accordance with local regulations.

Contaminated packaging Do not reuse empty containers.

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

United Kingdom - BE Page 10 / 13

Revision date 05-Sep-2022

Revision Number 3.04

EVO-STIK FLOORING ADHESIVE Supercedes Date: 11-Mar-2022

Land transport (ADR/RID)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable14.6 Special ProvisionsNone

IMDG

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Marine pollutantNP

14.6 Special Provisions None

14.7 Maritime transport in bulk Not applicable

according to IMO instruments

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide: Contains C(M)IT/MIT (3:1). May produce an allergic reaction

United Kingdom - BE Page 11 / 13

EVO-STIK FLOORING ADHESIVE Supercedes Date: 11-Mar-2022

Revision date 05-Sep-2022 Revision Number 3.04

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H310 - Fatal in contact with skin

H311 - Toxic in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H411 - Toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 05-Sep-2022

Indication of changes

United Kingdom - BE Page 12 / 13

EVO-STIK FLOORING ADHESIVE Supercedes Date: 11-Mar-2022 Revision date 05-Sep-2022 Revision Number 3.04

Revision note SDS sections updated, 3.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 13 / 13