

**RUST REMOVER** 

Page: 1

Compilation date: 07/06/2013

Revision date: 06/01/2020

Revision No: 3

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: RUST REMOVER

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road Cricklewood London

NW27TX

United Kingdom

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

## 1.4. Emergency telephone number

Emergency tel: .+44(0)2084504666 (Office hours only)

# Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; Skin Corr. 1B: H314

Most important adverse effects: Flammable liquid and vapour. Causes severe skin burns and eye damage.

# 2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H314: Causes severe skin burns and eye damage.

Hazard pictograms: GHS02: Flame

GHS05: Corrosion





Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P370+P378: In case of fire: Use media other than water to extinguish.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

## **RUST REMOVER**

Page: 2

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321: Specific treatment (see instructions on this label)

## 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

## 3.2. Mixtures

#### **Hazardous ingredients:**

#### PHOSPHORIC ACID

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	7664-38-2	-	Skin Corr. 1B: H314	41.080%
ETHANOL				
200-578-6	64-17-5	Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	24.570%
METHANOL				
200-659-6	Flam. Liq. 2: H225; Acute Tox. 3: H331; 1. Acute Tox. 3: H301; STOT SE 1: H370			

#### Section 4: First aid measures

## 4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and

footwear immediately unless stuck to skin.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. If unconscious and breathing is OK, place in the recovery

position. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### **RUST REMOVER**

Page: 3

#### 4.3. Indication of any immediate medical attention and special treatment needed

## Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Dry chemical powder. Alcohol resistant foam. Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Corrosive. Flammable. In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent

access to unauthorised personnel. Do not attempt to take action without suitable

protective clothing - see section 8 of SDS.

#### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

# 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a suitable container.

## 6.4. Reference to other sections

# Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Earth any equipment used in handling.

Use non-sparking tools.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep container tightly closed. Keep away from direct sunlight. Store in a cool, well

ventilated area.

Suitable packaging: Must only be kept in original packaging.

#### 7.3. Specific end use(s)

# Section 8: Exposure controls/personal protection

## 8.1. Control parameters

## **RUST REMOVER**

Page: 4

# **Hazardous ingredients:**

#### **ETHANOL**

## Workplace exposure limits:

### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1920 mg/m3	-	-	-

#### **METHANOL**

LIIZ	266 mg/m3	222 ma/m2		
UK	266 mg/m3	333 mg/m3	-	-

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure storage room has retention

walls.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). Self-contained breathing apparatus

must be available in case of emergency.

Hand protection: Protective gloves.

**Eye protection:** Ensure eye bath is to hand. Safety glasses.

Skin protection: Protective clothing.

# Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Alcoholic

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Miscible

Also soluble in: Methanol. Ethanol.

Viscosity: No data available.

Boiling point/range°C: 80 Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: 32 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: 1.120-1.175 @ 20C pH: No data available.

VOC g/l: No data available.

#### 9.2. Other information

Other information: No data available.

**RUST REMOVER** 

Page: 5

## Section 10: Stability and reactivity

## 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

#### 10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Flames.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong reducing agents.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

# **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

## **Hazardous ingredients:**

#### **ETHANOL**

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

## **METHANOL**

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

# Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat.

## **RUST REMOVER**

Page: 6

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## **Section 12: Ecological information**

## 12.1. Toxicity

Ecotoxicity values: No data available.

## 12.2. Persistence and degradability

Persistence and degradability: No data available.

## 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

# 12.4. Mobility in soil

Mobility: No data available.

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

Other adverse effects: No data available.

#### Section 13: Disposal considerations

## 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# **Section 14: Transport information**

## 14.1. UN number

UN number: UN1263

# 14.2. UN proper shipping name

Shipping name: PAINT

including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid

lacquer base

#### 14.3. Transport hazard class(es)

Transport class: 3

# 14.4. Packing group

Packing group: |

## **RUST REMOVER**

Page: 7

#### 14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: Yes

# 14.6. Special precautions for user

Tunnel code: D/E
Transport category: 1

## Section 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

#### Section 16: Other information

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H301: Toxic if swallowed.

H311: Toxic in contact with skin.

H314: Causes severe skin burns and eye damage.

H331: Toxic if inhaled.

H370: Causes damage to organs.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.