

Page 1/8

THE PERFECT FINISH

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.09.2020 Version number 176 Revision: 17.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: PLASTI-KOTE® PTFE-SPRAY 400 ML
- · Article number: 440.0071035.076
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC24 Lubricants, greases, release products
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTIP DUPLI B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

Nederland

Tel: +31 (0)561 694400 Fax: +31 (0)561 694411 e-mail: info@nl.motipdupli.com

- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

IRL: Beaumont Hospital - National Poisons Information Centre: Tel: +353 1 8092566

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Danger

(Contd. on page 2)

Printing date 11.09.2020 Version number 176 Revision: 17.12.2019

Trade name: PLASTI-KOTE® PTFE-SPRAY 400 ML

(Contd. of page 1)

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

| Dangerous components: | | |
|---|--|-----------|
| CAS: 64742-55-8 EINECS: 265-158-7 Index number: 649-468-00-3 Reg.nr.: 01-2119487077-29 | Distillates (petroleum), hydrotreated light paraffinic & Asp. Tox. 1, H304 | 25-<50% |
| CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21 | propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280 | 12.5-<20% |
| EC number: 918-481-9 Reg.nr.: 01-2119457273-39 | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics ❖ Asp. Tox. 1, H304 | 10-<12.5% |
| CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32 | butane Flam. Gas 1A, H220 Press. Gas (Comp.), H280 | 10-<12.5% |
| CAS: 109-66-0 EINECS: 203-692-4 Index number: 601-006-00-1 Reg.nr.: 01-2119459286-30 | pentane → Flam. Liq. 2, H225 → Asp. Tox. 1, H304 → Aquatic Chronic 2, H411 → STOT SE 3, H336 | 10-<12.5% |
| CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27 | isobutane Flam. Gas 1A, H220 Press. Gas (Comp.), H280 | 10-<12.5% |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

Printing date 11.09.2020 Version number 176 Revision: 17.12.2019

Trade name: PLASTI-KOTE® PTFE-SPRAY 400 ML

(Contd. of page 2)

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

No special measures required.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Printing date 11.09.2020 Version number 176 Revision: 17.12.2019

Trade name: PLASTI-KOTE® PTFE-SPRAY 400 ML

(Contd. of page 3)

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

109-66-0 pentane

WEL Long-term value: 1800 mg/m³, 600 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

- · Protection of hands: Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye protection: Not required.

| CHOMICA | | • 7 | 1 1 . 1 | , • |
|---------|---------|-------------|------------|------------|
| | (y • P) | iveiral and | chomical | properties |
| DECITOR | 7. II | eysicai ani | ı chemucui | properties |

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:
Colour:
Colour:
Codour:
Codour:
Codour:
Codour:
Codour:
Codour threshold:
Codo

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

· Flash point: Not applicable, as aerosol.

· Flammability (solid, gas): Not applicable.

• Ignition temperature: $>200 \, ^{\circ}C \, (>392 \, ^{\circ}F)$

· Decomposition temperature: Not determined.

· Explosive properties: Not determined.

· Explosion limits:

 Lower:
 0.6 Vol %

 Upper:
 10.9 Vol %

• Vapour pressure at 20 °C (68 °F): 3500 hPa (2625.2 mm Hg)

• Density at 20 °C (68 °F): 0.7 g/cm³ (5.8 lbs/gal)

· Relative density Not determined.

(Contd. on page 5)

Printing date 11.09.2020 Version number 176 Revision: 17.12.2019

Trade name: PLASTI-KOTE® PTFE-SPRAY 400 ML

| | | (Contd. of page |
|---|--|-----------------|
| · Vapour density | Not determined. | |
| · Evaporation rate | Not applicable. | |
| · Solubility in / Miscibility with | | |
| water: | Not miscible or difficult to mix. | |
| · Partition coefficient: n-octanol/water: | Not determined. | |
| · Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |
| · Solvent content: | | |
| Organic solvents: | 65.0 % | |
| VOC (EC) | | |
| | 438.8 g/l | |
| · VOC-EU% | 65.00 % | |
| · Solids content: | 3.3 % | |
| 9.2 Other information | No further relevant information available. | |

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC50 1 | · LD/LC50 values relevant for classification: | | |
|-------------|---|--|--|
| Hydrocarb | ons, C10-C | 13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | |
| Oral | LD50 | >5000 mg/kg (rat) | |
| Dermal | LD50 | >3000 mg/kg (rab) | |
| Inhalative | LC50 / 4 h | >4951 mg/m3 (rat) | |
| 109-66-0 р | 109-66-0 pentane | | |
| Oral | LD50 | >5000 mg/kg (rat) | |
| Inhalative | LC50 / 4h | 25.3 mg/l (rat) | |

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- $\cdot \textit{Carcinogenicity Based on available data, the classification criteria\ are\ not\ met.}$
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- $\cdot \textbf{STOT-single exposure } \textit{Based on available data, the classification criteria are not met.} \\$
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

GB

Printing date 11.09.2020 Version number 176 Revision: 17.12.2019

Trade name: PLASTI-KOTE® PTFE-SPRAY 400 ML

(Contd. of page 5)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

109-66-0 pentane

EC50 / 48 h | 9.7 mg/l (daphnia magna)

EC50 / 96 h 4.26 mg/l (fish)

LC50 / 96 h 4.26 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| · European | waste catalogue |
|------------|--------------------|
| 20 01 13* | solvents |
| 15 01 04 | metallic packaging |

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Buildup of explosive mixtures possible without sufficient ventilation.

| · 14.1 UN-Number | | |
|--------------------------------|---------------------|--|
| · ADR, IMDG, IATA | UN1950 | |
| · 14.2 UN proper shipping name | | |
| $\cdot ADR$ | 1950 AEROSOLS | |
| · IMDG | AEROSOLS | |
| \cdot IATA | AEROSOLS, flammable | |

i. on page /

Printing date 11.09.2020 Version number 176 Revision: 17.12.2019

Trade name: PLASTI-KOTE® PTFE-SPRAY 400 ML

(Contd. of page 6) · 14.3 Transport hazard class(es) $\cdot ADR$ · Class 2 5F Gases. · Label 2.1 · IMDG, IATA 2.1 · Class · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA not regulated · 14.5 Environmental hazards: Not applicable. · 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): · EMS Number: F-D,S-USW1 Protected from sources of heat. · Stowage Code SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: · Segregation Code Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · Limited quantities (LQ) 1LCode: E0 · Excepted quantities (EQ) Not permitted as Excepted Quantity Not permitted as Excepted Quantity · Transport category · Tunnel restriction code D· Limited quantities (LQ) 1L· Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity (Contd. on page 8)

Printing date 11.09.2020 Version number 176 Revision: 17.12.2019

Trade name: PLASTI-KOTE® PTFE-SPRAY 400 ML

(Contd. of page 7)

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.