



Iloform TDN 81

Neat forming oil

Description

Castrol Iloform™ TDN 81 is a medium viscosity, chlorinated, heavy duty forming fluid. It is a blend of high performance extreme pressure and lubricity additives in a fully solvent refined paraffinic mineral oil.

Application

Iloform TDN 81 is specially formulated for use in heavy duty deep drawing applications where extreme performance is required.

It is suitable for use on medium to heavy gauge steels, stainless steel, and nickel alloy steels, as well as aluminium and aluminium alloys.

Iloform TDN 81 is also recommended for use in stainless steel and alloy steel tube cold pilgering operations, where it is applied as an outer diameter roll lubricant, as well as machine gear box lubricant.

Advantages

- Contains high performance, extreme pressure additives, which provide very high resistance to temperature and pressure, and high resistance to wear. Enhanced tool and die life, cuts downtime and reduces tooling costs
- Provides a homogenous and tenacious lubricating film. Maintains excellent performance in high throughput, or multi stage operations. Consistent, high surface quality
- Flexibility. Suitable for use on a wide range of applications and materials. Allows potential for product rationalisation.
- Low odour and light colour. Excellent operator acceptance.

Characteristics

Typical Characteristics

Name	Method	Units	L08034GCC
Density @ 15C, Relative	ASTM D4052	g/ml	1.175
Appearance	Visual	-	limpid liquid / clear amber
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	140
Colour, Visual	Visual	-	-
Chlorine, % wt	X-Ray	% wt	-

The above figures are typical values and do not constitute a specification

User Advice

Iloform TDN 81 can be cleaned using aqueous alkaline or solvent cleaners.

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

Iloform TDN 81

12 Apr 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 717 Bourke Street, Docklands Vic 3008
Technical Advice Line: 1300 557 998 Customer Service: 1300 722 088

<http://msdspd.castrol.com>

Page: 2/2