

Male x Female Reducing Bush (241)



Forms I, II, III are available only as marked under column "Form", "Form I" can also be supplied with continuous internal thread (=241D).

ST... these types of fittings are made from steel (galvanised finished = electroplated) and not suitable for drinking water installation.



Black, BSPT Male x BSPP Female

Part Code	Thread (1)	Thread (2)	Form	a mm	b mm	z mm	s mm
GF241-14-18N*	1/4"	1/8"	I	20		13	17
GF241-38-18N*	3/8"	1/8"	I	20		13	19
GF241-38-14N*	3/8"	1/4"	I	20		10	19
GF241-12-18N	1/2"	1/8"	II	24		17	23
GF241-12-14N	1/2"	1/4"	I	24		14	23
GF241-12-38N	1/2"	3/8"	I	24		14	23
GF241-34-14N	3/4"	1/4"	II	26		16	30
GF241-34-38N	3/4"	3/8"	II	27		16	30
GF241-34-12N	3/4"	1/2"	I	26		13	30
GF241-1-14N	1"	1/4"	II	29		19	36
GF241-1-38N	1"	3/8"	II	29		19	36
GF241-1-12N	1"	1/2"	II	29		16	36
GF241-1-34N	1"	3/4"	II	29		14	36
GF241-114-38N	1.1/4"	3/8"	II	31		21	46
GF241-114-12N	1.1/4"	1/2"	II	31		18	46
GF241-114-34N	1.1/4"	3/4"	II	31		16	46
GF241-114-1N	1.1/4"	1"	II	31		14	46
GF241-112-38N	1.1/2"	3/8"	II	31		21	50
GF241-112-12N	1.1/2"	1/2"	II	31		18	50
GF241-112-34N	1.1/2"	3/4"	II	31		16	50
GF241-112-1N	1.1/2"	1"	II	31		14	50
GF241-112-114N	1.1/2"	1.1/4"	I	33		12	50
GF241-2-12N	2"	1/2"	III	35	48	33	65
GF241-2-34N	2"	3/4"	III	35	48	35	65
GF241-2-1N	2"	1"	II	37		20	65
GF241-2-114N	2"	1.1/4"	II	37		18	65
GF241-2-112N	2"	1.1/2"	II	37		18	65
GF241-212-1N	2.1/2"	1"	III	40	54	37	80
GF241-212-114N	2.1/2"	1.1/4"	III	40	54	37	80
GF241-212-112N	2.1/2"	1.1/2"	II	40		21	80
GF241-212-2N	2.1/2"	2"	II	40		16	80
GF241-3-1N	3"	1"	III	44	59	42	95
GF241-3-114N	3"	1.1/4"	III	44	59	40	95
GF241-3-112N	3"	1.1/2"	III	44	59	40	95
GF241-3-2N	3"	2"	II	44		20	95
GF241-3-212N	3"	2.1/2"	II	44		17	96
GF241-4-2N	4"	2"	III	51	69	45	120
GF241-4-212N	4"	2.1/2"	III	51	69	42	120
GF241-4-3N	4"	3"	II	51		21	120
GF241-6-4N	6"	4"					

Galvanised, BSPT Male x BSPP Female

Part Code	Thread (1)	Thread (2)	Form	a mm	b mm	z mm	s mm
GF241-14-18*	1/4"	1/8"	I	20		13	17
GF241-38-18*	3/8"	1/8"	I	20		13	19
GF241-38-14*	3/8"	1/4"	I	20		10	19
GF241-12-18	1/2"	1/8"	II	24		17	23
GF241-12-14	1/2"	1/4"	I	24		14	23
GF241-12-38	1/2"	3/8"	I	24		14	23
GF241-34-14	3/4"	1/4"	II	26		16	30
GF241-34-38	3/4"	3/8"	II	27		16	30
GF241-34-12	3/4"	1/2"	I	26		13	30
GF241-1-14	1"	1/4"	II	29		19	36
GF241-1-38	1"	3/8"	II	29		19	36
GF241-1-12	1"	1/2"	II	29		16	36
GF241-1-34	1"	3/4"	II	29		14	36
GF241-114-38	1.1/4"	3/8"	II	31		21	46
GF241-114-12	1.1/4"	1/2"	II	31		18	46
GF241-114-34	1.1/4"	3/4"	II	31		16	46
GF241-114-1	1.1/4"	1"	II	31		14	46
GF241-112-38	1.1/2"	3/8"	II	31		21	50
GF241-112-12	1.1/2"	1/2"	II	31		18	50
GF241-112-34	1.1/2"	3/4"	II	31		16	50
GF241-112-1	1.1/2"	1"	II	31		14	50
GF241-112-114	1.1/2"	1.1/4"	I	33		12	50
GF241-2-12	2"	1/2"	III	35	48	33	65
GF241-2-34	2"	3/4"	III	35	48	35	65
GF241-2-1	2"	1"	II	37		20	65
GF241-2-114	2"	1.1/4"	II	37		18	65
GF241-2-112	2"	1.1/2"	II	37		18	65
GF241-212-1	2.1/2"	1"	III	40	54	37	80
GF241-212-114	2.1/2"	1.1/4"	III	40	54	37	80
GF241-212-2	2.1/2"	2"	II	40		21	80
GF241-3-1	3"	1"	II	40		16	80
GF241-3-114	3"	1.1/4"	III	44	59	42	95
GF241-3-112	3"	1.1/2"	III	44	59	40	95
GF241-3-2	3"	2"	II	44	59	40	95
GF241-3-212	3"	2.1/2"	II	44		20	95
GF241-4-2	4"	2"	II	44		17	96
GF241-4-212	4"	2.1/2"	III	51	69	45	120
GF241-4-3	4"	3"	III	51	69	42	120
GF241-6-4	6"	4"	II	51		21	120



*Stainless Steel