




CATALOGUE > Release 8.7

CONNECTION > Series 6000 super-rapid fittings

Fittings Mod. 6610


Single Banjo



DIMENSIONS									
Mod.	A	C	F	M	O	V	W	Weight (g)	assembled with Mod.
6610 4-M5	4	5	9	19	9	5.1	□ 9	9	1631
6610 4-M6	4	5	9	19	9	5.1	□ 9	8	SCU, SVU, SCO...
6610 4-1/8	4	7.5	9	21.5	14.5	9.8	Ø 14	14	1631, 1635, SCU, SVU, SCO...
6610 5-M5	5	5	10	20	9	5.1	□ 9	9	1631
6610 5-M6	5	5	10	20	9	5.1	□ 9	8	SCU, SVU, SCO...
6610 5-1/8	5	8	10	23	14.5	9.8	Ø 14	16	1631, 1635, SCU, SVU, SCO...
6610 6-M5	6	6.5	12.7	22.5	9	5.1	Ø 10	12	1631
6610 6-M6	6	6.5	12.7	22.5	9	5.1	Ø 10	12	SCU, SVU, SCO...
6610 6-1/8	6	8	12.7	24	14.5	9.8	Ø 14	16	1631, 1635, SCU, SVU, SCO...
6610 6-1/4	6	10	12.7	26	14.5	13.2	Ø 18	19	1631, 1635, SCU, SVU, SCO...
6610 8-1/8	8	8	14.2	25.5	14.5	9.8	Ø 14	19	1631, 1635, SCU, SVU, SCO...
6610 8-1/4	8	10	14.2	27.5	14.5	13.2	Ø 18	22	1631, 1635, SCU, SVU, SCO...
6610 8-3/8	8	11	14.2	28.5	14.5	16.7	Ø 21	23	1631, 1635, SCU, SVU, SCO...
6610 10-1/4	10	8.8	16.5	29	14.5	13.2	Ø 18	22	1635, SCU, SVU, SCO...
6610 10-3/8	10	10.3	16.5	30.5	14.5	16.7	Ø 21	23	1635, SCU, SVU, SCO...
6610 12-1/2	12	12.8	16.5	32	14.5	21	Ø 26	37	1635

Fittings Mod. 6811

Metric Male Adaptor Sprint®



DIMENSIONS								
Mod.	G	D	H	T	L	SW	Weight (g)	
6811 4-M5	4	M5	4	16.5	24.5	8	3	*
6811 4-1/8	4	G1/8	5.5	16.5	27.8	12	10	
6811 5-1/8	5	G1/8	5.5	18	29.3	12	9	
6811 5-1/4	5	G1/4	7	18	31	14	11	
6811 6-1/8	6	G1/8	5.5	18	29.3	12	10	
6811 6-1/4	6	G1/4	7	18	31	14	12	
6811 8-1/8	8	G1/8	5.5	20.5	31.8	12	12	
6811 8-1/4	8	G1/4	7	20.5	33.5	14	13	
6811 10-1/4	10	G1/4	7	23	36	14	16	
6811 10-3/8	10	G3/8	8	23	37.3	19	25	
6811 12-3/8	12	G3/8	8	24	38.3	19	25	
6811 14-1/2	14	G1/2	9	28	44	22	39	

* = with O-Ring