

#### Description

An inoffensive, non-corrosive foam used in the inspection of pipework to prevent leaks passing unnoticed with potentially dangerous effects. It will detect any leaks instantly and is harmless to most materials as well as being safe to use with most other gases.

#### Benefits & Features

- Non-flammable water based
- Completely inert
- Will detect the smallest leaks
- Will not form combustible mixture with other gases
- Can be used with oxy-acetylene and LPG gases
- Non-corrosive
- Nitrogen propellant
- Easily removed – completely water soluble
- Conforms to BS EN ISO 14921 EU Regulations for use in Department of Transport testing stations

#### Directions for Use

Shake can well before use. Spray liberally onto suspected area of leak. A stream of bubbles will indicate the exact source of the leak.

#### Technical Data

Appearance:	Clear/white slightly foaming liquid
Odour:	Virtually odourless
Contents:	Blend of ethanediol, ethoxylated alcohol and corrosion prevention additive in demineralised water with nitrogen propellant
Flash Point:	<0°C
Solubility:	Soluble in water
Temperature Range:	Designed for use at ambient temperatures
Relative Density:	1.02
pH:	7-7.5
Flammability:	Extremely Flammable
Health & Safety:	Consult Safety Data Sheet (available at <a href="http://tygrisindustrial.com">tygrisindustrial.com</a> )
Storage:	Below 50°C
Pack Size:	12 x 300ml aerosols

#### Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

