

Description

Provides a tenacious lubricant film to exposed gears and wire ropes. A bituminous reinforced heavy duty lubricant formulated to protect and lubricate exposed gears, wire ropes and other moving parts. Exceptional penetrating and water resistance properties make it ideal for situations where exposure to weather is experienced and its tenacity resists throwing off during use.

Benefits & Features

- Highly resistant to throw off
- Water resistant for use in adverse weather conditions
- Good penetrating qualities
- Excellent lubricating power
- High pressure foaming discharge imparts excellent penetrative power
- Protects against corrosion, wear and salt
- Resistant to embrittlement over long usage

Directions for Use

Shake can well before use. Spray onto stationary parts from 20 to 30cm. The directional nozzle assists in accurate positioning of the lubricant.

Technical Data

Appearance:	Dark brown frothy foam drying to a sticky viscous state
Odour:	Mineral oil odour
Contents:	Blend of petroleum distillates, mineral oil, xylene, bitumen, anti-fling and extreme pressure additives, and hydrocarbon propellants
Flash Point:	<0°C
Solubility:	Insoluble in water
Temperature Range:	For use at ambient temperatures
Relative Gravity:	0.900
Flammability:	Extremely Flammable
Health & Safety:	Consult Safety Data Sheet (available at tygrisindustrial.com)
Storage:	Below 50°C
Pack Size:	12 x 400ml aerosols

Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

