

**DRAWSOL K15** 

Page: 1

Compilation date: 15/07/2020

Revision date: 06/08/2020

Revision No: 4

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: DRAWSOL K15
Product code: DRDSK15

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC25: Metal working fluids.

# 1.3. Details of the supplier of the safety data sheet

Company name: James Lister Limited

Spon Lane South

Smethwick West Midlands

B66 1QJ

Tel: 0121 553 2949

Email: sales@lister.co.uk

# 1.4. Emergency telephone number

Emergency tel: 0121 553 2949

(office hours only)

#### **Section 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification under CLP: Eye Dam. 1: H318; Lact.: H362; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Irrit.

2: H315; -: EUH066

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. Causes skin irritation. Causes

serious eye damage. May cause harm to breast-fed children. Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

### 2.2. Label elements

# Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H362: May cause harm to breast-fed children.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS05: Corrosion

GHS09: Environmental

[cont...]

DRAWSOL K15

Page: 2





Signal words: Danger

Precautionary statements: P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P263: Avoid contact during pregnancy and while nursing.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P362+P364: Take off contaminated clothing and wash it before reuse.

#### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

#### 3.2. Mixtures

#### Hazardous ingredients:

CHLORINATED PARAFFIN C14-C17 - REACH registered number(s): 01-2119519269-33-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
287-477-0	85535-85-9	-	Aquatic Chronic 1: H410; Aquatic Acute 1: H400; Lact.: H362; -: EUH066	50-75%

#### FATTY ACIDMONOETHANOLAMIDE ETHOXYLATE

-	26027-37-2	-	Eye Irrit. 2: H319	10-25%

#### 2-AMINOETHANOL

205-483-3	141-43-5	-	Acute Tox. 4: H332; Acute Tox. 4: H312;	1-5%
			Acute Tox. 4: H302; Skin Corr. 1B:	
			H314	

# Section 4: First aid measures

#### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

DRAWSOL K15

Page: 3

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe

pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

#### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

# 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised

personnel. Do not attempt to take action without suitable protective clothing - see section

8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

# 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

# Section 7: Handling and storage

DRAWSOL K15

Page: 4

# 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation or spread of mists in the air.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

#### 7.3. Specific end use(s)

Specific end use(s): PC25: Metal working fluids.

# Section 8: Exposure controls/personal protection

# 8.1. Control parameters

#### Hazardous ingredients:

# 2-AMINOETHANOL

## Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	2.5 mg/m3	7.6 mg/m3	-	-

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

# 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

# Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Liquid Colour: Amber

Odour: Perceptible odour

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Soluble

Viscosity: Viscous

Boiling point/range°C: No data available. Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: >180

DRAWSOL K15

Page: 5

Part.coeff. n-octanol/water: No data available.

**Autoflammability°C:** No data available. **Vapour pressure:** No data available.

Relative density: 1.14 pH: No data available.

VOC g/I: No data available.

#### 9.2. Other information

Other information: No data available.

#### Section 10: Stability and reactivity

# 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

# 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

# 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

# **Hazardous ingredients:**

# **CHLORINATED PARAFFIN C14-C17**

DERMAL	RAT	LD50	>4000	mg/kg
ORAL	RAT	LD50	>4000	mg/kg
VAPOURS	RAT	LD50	>48170	mg/kg

#### 2-AMINOETHANOL

IVN	RAT	LD50	225	mg/kg
ORL	MUS	LD50	700	mg/kg
ORL	RAT	LD50	1720	mg/kg

DRAWSOL K15

Page: 6

SCU	RAT	LD50	1500	ma/ka
				9,9

#### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

#### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe

pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# Section 12: Ecological information

# 12.1. Toxicity

# Hazardous ingredients:

# **CHLORINATED PARAFFIN C14-C17**

ALGAE	96H ErC50	>3.2	μg/l
Daphnia magna	-	5.9	μg/l

#### 12.2. Persistence and degradability

Persistence and degradability: No data available.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

# 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

# 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

# 12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

# Section 13: Disposal considerations

# 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

DRAWSOL K15

Page: 7

Disposal of packaging: Empty containers should be taken to an approved waste handling site for recycling or

disposal

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# **Section 14: Transport information**

#### 14.1. UN number

UN number: UN3082

#### 14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

#### 14.3. Transport hazard class(es)

Transport class: 9

# 14.4. Packing group

Packing group: III

#### 14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

# 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: Transport category: 3

# **Section 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Product is not subject to authorisation under REACh.

#### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

# **Section 16: Other information**

### Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation

(EU) 2015/830

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

# DRAWSOL K15

Page: 8

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H362: May cause harm to breast-fed children.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.