

 <p><b>listerlube</b> since 1874 www.lister.co.uk</p> <p><b>Specification Sheet</b></p>	<p><b>listerlube</b> <b>EP90 GL5</b> <b>Hypoid Gear Oil</b></p>
<p>James Lister &amp; Sons Ltd. Spon Lane South, Smethwick, West Midlands. B66 1QJ</p>	

#### General

listerlube EP90 GL5 Hypoid Gear Oil is an active, extreme pressure lubricant for hypoid and other enclosed gears where sliding and pressure conditions are extremely severe. It is not suitable for gears incorporating yellow metals.

#### Appearance

Dark brown opaque liquid with characteristic odour.

#### Viscosity

listerlube EP90 GL5 Hypoid Gear Oil is blended to a SAE90 viscosity, typically 220 cSt @ 40°C.

#### Performance Characteristics

listerlube EP90 is available as GL-4 and GL-5. Our service engineers will help new users as to which grade is applicable. As a guide the following information may help.

GL-4 Equivalent to the former MIL-L-2105 specification. Typical applications include manual transmissions spiral bevel and hypoid gears where moderate service prevails.

GL-5 Equivalent to present MIL-L-2105 D specification. It is the most commonly specified and available type of automotive gear lubricant and is used for moderate and severe service in hypoid or similar types of gears.

#### Health & Safety

Hazard markings not required.