

	<h1>listerlube</h1> <h2>Hydraulic Oil 32</h2>
James Lister & Sons Ltd. Spon Lane South, Smethwick, West Midlands. B66 1QJ	

### General

listerlube Hydraulic Oil 32 is a high-performance hydraulic oil based on very highly refined mineral oil and offers outstanding antiwear, corrosion protection and antioxidant characteristics. In addition, the product exhibits superior air release and demulsification as well as good filtration properties even when extremely fine filters are used. listerlube Hydraulic Oil 32 is a high viscosity index product and will therefore give effective performance in high temperature environments. It is designed principally for industrial applications but can be used whenever the following specifications are required:

### Specifications

DIN 51524 part 2 and 3 (HLP, HVLP)  
AFNOR NF E 48-603 (HM, HV)  
SIS SS 155434  
VDMA 24318  
Hoesch HWN 2333  
Thyssen TH N-256132

CETOP RP 91 H (HM, HV)  
SEB 181 222  
U.S. Steel 126 and 127  
Sperry Vickers M-2950-S and I-286-S  
Denison Filterability TP 02100

In addition listerlube Hydraulic Oil 32 can be used as a lubricating oil for a wide range of industrial applications.

### Physical Characteristics

Kinematic Viscosity	@ 0°C:	352 cSt
	@ 40°C:	32 cSt
	@ 100°C:	5.29 cSt
Viscosity Index:		95
Flash Point (Closed):		195°C (minimum)
Pour Point:		-6°C